



## XV7 VESA IPC Fanless

### XV7 VESA IPC Fanless

	<b>XV715</b>
<b>DisplaySize</b>	15"
<b>Technology</b>	TFT
<b>Colors</b>	262 K
<b>Backlight</b>	LED
<b>Life (min. at 25 °C)</b>	50.000 h
<b>Resolution</b>	1024 x 768 pixels
<b>Touch Screen Type</b>	Analog resistive (5 wires)
<b>CPU Fanless</b>	Intel® ATOM Dual Core N-2800 1.86 GHz
<b>Chipset</b>	Intel® NM10
<b>DMI</b>	2,5 GT/s
<b>RAM</b>	up to 4 GB DDR3 DIMM 204 pin
<b>Removable Hard disk / SSD (opt.)</b>	min. 250 GB SATA 2,5" / SSD 16 GB
<b>Compact Flash Slot Internal (opt.)</b>	1 x
<b>Compact Flash Slot External (opt.)</b>	1 x
<b>RS232 serial port</b>	1 x
<b>RS485 serial port</b>	1 x
<b>USB on front (2.0) IP66</b>	1 x
<b>USB on rear (2.0)</b>	2 x
<b>Green led on front</b>	1 x
<b>PS/2 keyboard / mouse port</b>	-
<b>Mini PCIe</b>	1 x
<b>Wi-fi card (optional)</b>	miniPCIe 1 x
<b>Video port</b>	1 x VGA
<b>Audio port</b>	-
<b>Ethernet port RJ45</b>	2 x Ethernet 10/100/1000 Mbit
<b>External (W x H x D) (mm)</b>	425 x 300 x 77 (mm)
<b>Cut-out (W x H) (mm)</b>	-
<b>Back-up with battery</b>	1 x
<b>Power supply</b>	18...30 Vdc max 85 W
<b>Power consumption (24 Vdc - basic config)</b>	43 W
<b>Protection level</b>	IP 66 on front / IP54 on rear
<b>Storage temperature (°C)</b>	-20...+65
<b>Operating temperature (°C)</b>	0...+50



## XV7 VESA IPC Fanless

<b>Weight (kg)</b>	7,5
<b>Humidity</b>	90%
<b>Certifications</b>	CE, Environment EN 60068-2-6/27/30 / Immunity EN 61000-6-2 / Emissions 61000-6-4
<b>Operating system</b>	Win7 - Wes7 - Wes 2009 - WinXP Professional for Embedded