



Industrial Automation - Products & Configurations

MHR100-TFX MONITOR		POWER [W]
Basic configuration	LCD TFT 12,1" • touch-screen with USB interface • Stainless Steel TrueFlat front panel • integrated remotation (RX) • remotation module (TX) for DVI-D and USB 2.0 signals • Without remotation cable • 24V DC isolated power supply • without cables • 12 months warranty	21

DISPLAY & TOUCH-SCREEN	↓		
	12,1" LCD TFT 4:3 • SVGA, 800x600, 16M colors • backlight LED, 500 cd/m2 • Viewing angle L:R/U:L (typ): 80°:80°/80°:60°		
	12,1" Touch-Screen • 5 wires resistive technology • USB I/F		
	12,1" LCD TFT 4:3 • XGA, 1024x768, 16M colors • backlight LED, 600 cd/m2 • Viewing angle L:R/U:L (typ): 80°:80°/70°:70°		+ 5
	12,1" Touch-Screen • 5 wires resistive technology • USB I/F		
	15" LCD TFT 4:3 • XGA, 1024x768, 16M colors • backlight LED, 500 cd/m2 • Viewing angle L:R/U:L (typ.): 85°:85°/85°:85°		+ 8
	15" Touch-Screen • 5 wires resistive technology • USB I/F		
	17" LCD TFT 5:4 • SXGA, 1280x1024, 16M colors • backlight LED, 350 cd/m2 • Viewing angle L:R/U:L (typ): 85°:85°/80°:80°		+ 17
17" Touch-Screen • 5 wires resistive technology • USB I/F			
19" LCD TFT 5:4 MVA • SXGA 1280x1024, 16M colors • backlight LED, 300 cd/m2 • Viewing angle L:R/U:L (typ): 89°:89°/89°:89°		+ 28	
19" Touch-Screen • 5 wires resistive technology • USB I/F			

REMOTATION MODULE (TX)	↓	
	Remotation module (TX) for DVI-D and USB 2.0 signals • 24V DC power supply • For wall (standard and book) and DIN guide (book) mounting	

POWER SUPPLY	↓	
	Input voltage 24V DC • isolated	
Input voltage 110/230V AC • autoranging		+ 0

CABLES for REMOTATION > note 1

		POWER [W]
PATCH CABLES for REMOTATION	Cables kit 0,9 mt (DVI-D 1 mt / USB 2.0 0,9 mt)	-
CABLES for REMOTATION STATIC LAYING	Cable 15 mt • Cat 5e SF/UTP type • for static laying • UL certificate > note 2	-
	Cable 20 mt • Cat 5e SF/UTP type • for static laying • UL certificate > note 2	-
	Cable 30 mt • Cat 5e SF/UTP type • for static laying • UL certificate > note 2	-
	Cable 50 mt • Cat 5e SF/UTP type • for static laying • UL certificate > note 2	-
	Cable 100 mt • Cat 5e SF/UTP type • for static laying • UL certificate > note 2	-

OPTIONS

WARRANTY EXTENSION	↓		
	Warranty extension to 18 months on basic system and its variants		
	Warranty extension to 24 months on basic system and its variants		
Warranty extension to 36 months on basic system and its variants			

NOTES
For power consumption calculation we recommend to read the tips on pg. 4. The power values does not include the absorbed power of USB devices connected to the ports.
1: Customer can buy patch and remotation cables from ASEM or supply it by other suppliers.
2: SF/UTP (Shielded Foil Unshielded Twisted Pair) is for Ethernet cable and means that the cable is shielded and made by twisted pair copper wires.



TECHNICAL SPECIFICATIONS	
Case	Panel mount
Front panel	TrueFlat stainless steel 1.4301 surface brushing grain 180 medium • Polyester Autoflex EB A180 RAL 7035 color • ASEM logo serigraph printed
Touchscreen	5 wires resistive technology • overlaminated with OCA (Optical Clear Adhesive) • on board controller • USB I/F
Overall dimensions & weight	See details on the related section
Frontal protection	IP66
Power supply	DC Input voltage 18+36V DC • isolated
	AC Input voltage 90+264 V AC • isolated • Autoranging
Rear access interfaces	1 x RJ45 (remotation input) • 2 x USB 2.0 (Type A)
Environmental specifications	Operating temperature: 0° ÷ +50°C • Storage temperature: -5° ÷ +60°C • Humidity: 80% (non-condensing)
Approvals	CE (EN 55022, EN 61000-3-2/3, EN 55024, EN 60950-1) • cULus LISTED (UL508) pending
Standard warranty	12 months • Warranty management by ASEM headquarters

