

### EW100AA

HMI for Visualization /Control and Remote Viewing

	EW104AA	EW107AA	EW112AA	EW115AA
Display Size	4,3"	7"	12,1"	15,6"
Display Technology	TFT			
Display Colors	262k	16M		
Display Backlight	LED			
Display Brightness (cd/m <sup>2</sup> )	400	600	400	300
Display Resolution (pixel)	480 x 272	800 x 480	1280 x 800	1366 x 768
Backlight life(hours)	50k			
Processor	ARM Cortex A8			
RAM	256 MB DDR3		512 MB DDR3	
Flash	3GB			
Serial Ports	SP1 RS232/485-MPI-COM0 ; SP2 RS232/485-MPI-COM0 ; CAN ; Profibus			
USB Ports	1 x USB Host + 1 x USB Device		2 x USB Host + 1 x USB Device	
Slot	1 x SDHC/MMC			
Power Supply (Vdc)	12-32 (A version) / 18-32 (B-C versions)			
Consumption (W)	4	7	15	19
Operating Temperature (°C)	-10 ... + 50 non condensing			
Storage Temperature (°C)	-20 ... + 65			
Humidity	<90%(non condensing)			
External dimensions (W/H/D) (mm)	166 x 112 x 46 (61 with double port)	202 x 142 x 46	341 x 239 x 49	437 x 286 x 54,5
Cut-out dimensions (W/H) (mm)	158,5 x 104,5	195,0 x 135,0	326,0 x 227,0	422,5 x 271,5
Weight (kg)	0,5	0,8	2,5	4,5
Protection degree (front)	IP 66	IP 66	IP 66	IP 66
Certifications	CE / EN60068-2-6 / EN60068-2-27 / Humidity EN60068-2-30 / cULus (Certificate no. E189179) / EAC/ Directive 94/9/EC Atex Group II - Category 3 G-D Zone 2/22			