



XS7 Panel Dynamic C2D

XS7 Industrial Panel Dynamic C2D

	XS712	XS715	XS717	XS719
Display Technology	TFT			
Colors	262 K		16,7 M	
Backlight	LED			
Life (min. at 25 °C)	50.000 h			
Resolution pixel	800x600 (SVGA) - 1024x768 (XGA)	1024 x 768 pixels	1280 x 1024 pixels	
Type	Analog resistive (5 wires)			
CPU Fanless	Intel® Core2Duo Penryn P8400 2,26GHz / Intel® Celeron Core Duo Penryn T3100 1,9GHz			
Chipset	GM45 + ICH9M			
FSB	1066 / 800 MHz			
RAM	up to 8GB DDR3 SODIMM 204pin			
Hard disk / SSD (opt.)	min. 250 GB SATA 2,5" / SSD 16 GB			
Internal (opt.)	1 x			
External (opt.)	1 x			
RS232 serial port	1 x			
RS485 serial port	1 x			
USB on front (2.0) IP66	1 x			
USB on rear (2.0)	4 x			
Green led on front	1 x			
PS/2 keyboard / mouse port	1 x			
PCI Slot 1 (opt.)	1 x			
PCI Slot 2 (opt.)	1 x			
Mini PCIe (opt.)	-			
PCIe slot 1x (opt.)	1 x			
wi-Fi card (opt.)	PCI / USB / PCIe 1x		PCI / USB / PCIe 1x	
Video port	1 x VGA + 1xDVI-I (single-link digital signal only)			
Audio port	MIC IN + Line IN + Line OUT			
Ethernet ports RJ45	2 x Ethernet 10/100/1000 Mbit			
External (W x H x D) (mm)	336 x 256 x 81	425 x 300 x 85,5	446 x 346 x 84	508 x 384 x 92,5



XS7 Panel Dynamic C2D

Cut-out (WxH) (mm)	321 x 240	393 x 275	426 x 326	477 x 355
Back-up with battery	1 x			
Power supply	18...30 Vdc max 75 W	18...30 Vdc max 85 W	18...30 Vdc max 95 W	18...30 Vdc max 95 W
Power consumption (24 Vdc - basic config - NO PCI CARDS)	48/58 W	55/65 W	67/77 W	
Protection level	IP 66 frontal			
Operating temperature (°C)	0...+50	0...+50	0...+50	0...+50
Storage temperature (°C)	-20...+65			
Weight (kg)	~ 5	~ 6,5	~ 9	~ 11
Humidity	90%			
Certifications	CE, Atex (Group II - cat.3 G D) / Environment EN 60068-2-6/27/30 / Immunità EN 61000-6-2 / Emissioni 61000-6-4			
Optional kits				
Frontal INOX with True-flat Touch screen	12,1" / 15" / 19" - No LED/USB frontal			
RAID 2xHDD function	Yes			
Removable HDD/SSD	Yes			
DVD-RW SATA	External	Internal		
Operating system	WIN7 - WES2009 - Win® XP Pro SP3 MUI			