



EW410 Compact

Power, design and Versatility

EW410 Compact

Aluminium Enclosure	Heavy Alu extrusion chassis Aluminum Heat-Sink LED green on/off Selection ATX/APO via Bios On/Off push-button LED blue HDD Lockable power connector
CPU Fanless	Atom Dual Core D2550 1,86 GHz
Chipset	NM10 DMI 2,5GT/s
GPU embedded	GMA3650 1920x1200 max. resolution
RAM	RAM 2GB DDR3 1066 MHz on board
I/F	2 x RS232/422/485 Sub-D 9 pin 4 x USB ver. 2.0 1 x SIM slot 2 x Ethernet 1 Gbit RJ45 - Intel 82574L 3 x MiniPCle slot (1 x mSATA) 1 x DVI-I 1 x Line Out / Mic In 1 x CFast slot external access
Drives	CFast/mSATA
Operating Temperature (°C)	0...60
StorageTemperature (°C)	-40...80
Humidity	85%(non condensing)
Weight (kg)	0,7
Power supply (Vdc)	9 ... 26 Vdc max 20W
Dimensions (W/H/D) (mm)	161x108x32
Certifications	CE / EN61000-6-2 / EN61000-6-4 / EN60068-2-6/27/30 / Gost / IP20