


BM3400/S2

fanless

Industrial Automation - Products & Configurations

BM3400/S2 D0 BASIC SYSTEM				POWER [W]	
Basic Configuration		Intel® Celeron® dual core G3900E 2,40 GHz • 4GB RAM • fanless • UBIQUITY BASIC Win32/64 runtime • without predisposition to extractable drives • 24V DC isolated power supply • 1 slot PCIe x4 + 1 slot PCI • 12 month warranty		56	
BM3400/S2 D1 BASIC SYSTEM				POWER [W]	
Basic Configuration		Intel® Celeron® dual core G3900E 2,40 GHz • 4GB RAM • fanless • UBIQUITY BASIC Win32/64 runtime • with predisposition to 1 extractable drive in left position • 24V DC isolated power supply • 1 slot PCIe x4 + 1 slot PCI • 12 month warranty		56	
BM3400/S2 D2 BASIC SYSTEM				POWER [W]	
Basic Configuration		Intel® Celeron® dual core G3900E 2,40 GHz • 4GB RAM • fanless • UBIQUITY BASIC Win32/64 runtime • with predisposition to 2 extractable drives • 24V DC isolated power supply • 1 slot PCIe x4 + 1 slot PCI • 12 month warranty		56	
REMOTE ASSISTANCE	D0	D1	D2	ASEM UBIQUITY BASIC Win32/64 runtime	
	•	•	•		
PROCESSORS	•	•	•	Intel® Celeron® G3900E • 2,40 GHz, 2MB L2 cache • 2 cores, 2 threads • Soldered on-board	
	•	•	•	Intel® Core™ i3-6100E • 2,70 GHz • 3MB smart cache • 2 cores, 4 threads • Soldered on-board	+ 0
	•	•	•	Intel® Core™ i5-6440EQ • 2,70 GHz (3,40 GHz Turbo) • 6MB smart cache • 4 cores, 4 threads • Soldered on-board	+ 0
	•	•	•	Intel® Core™ i7-6820EQ • 2,80 GHz (3,50 GHz Turbo) • 8MB smart cache • 4 cores, 8 threads • Soldered on-board	+ 13
RAM MEMORY	•	•	•	4 GB • 1 module SODIMM DDR4-2133	
	•	•	•	8 GB • 2 x 4 GB modules SODIMM DDR4-2133	+ 1
	•	•	•	16 GB • 2 x 8 GB modules SODIMM DDR4-2133	+ 2
	•	•	•	32 GB • 2 x 16 GB modules SODIMM DDR4-2133	+ 3
INTERNAL PSU	•	•	•	Without UPS (uninterruptible power supply)	
	•	•	•	With UPS (uninterruptible power supply) • integrated in power supply section • batteries kit not included > note 1	+ 1
EXPANSION SLOTS	•	•	•	1 slot PCIe x4 + 1 slot PCI half size • on riser card • expansion cards with power consumption max di 5W each	
	•	•	•	2 x PCIe x4 half size • on riser card • expansion cards with power consumption max di 5W each	+ 0
OPTIONS				POWER [W]	
TPM	•	•	•	TPM - Trusted Platform Module	0
CFAST	•	•	•	CFAST SATA	1
SSD mSATA	•	•	•	SSD mSATA, SATA III, 6Gb/s (Solid State Disk), MLC	2
HDD/SSD 2,5"	•	•	•	1 x HDD/SSD 2,5" SATA III internal installation kit (HDD/SSD not included)	-
	•	•	•	2 x HDD/SSD 2,5" SATA III internal installation kit (HDD/SSD not included)	-
	•	•	•	1 x HDD/SSD 2,5" SATA III extractable drawer (HDD/SSD not included) • installation in left predisposition	-
	•	•	•	2 x HDD/SSD 2,5" SATA III extractable drawers (HDD/SSD not included)	-
	•	•	•	SSD 2,5" SATA	5
	•	•	•	HDD 2,5" SATA	6
COMMUNICATION PORTS	•	•	•	1 x RS232/422/485 (DB15M) • 1 x USB 2.0 > note 2	1
	•	•	•	1 x RS232/422/485 (DB15M) isolated • 1 x USB 2.0 > note 2	1
	•	•	•	2 x RS232 (DB9M) > note 2	2
	•	•	•	2 x USB 2.0 > note 2	0
REMOTE VIDEO LINK	•	•	•	1 x additional video output RVL - Remote Video Link • Remotation up to 100m of DVI-D and USB 2.0 signals • without cables > note 3	3
UPS BATTERIES KIT	•	•	•	Batteries kit for detached systems mounting (wall mount) • 30cm cable included	15
	•	•	•	Batteries kit for detached mounting (wall mount) • 100cm cable included	15
WARRANTY EXTENSION	•	•	•	Warranty extension to 18 months on basic system and its variants	
	•	•	•	Warranty extension to 24 months on basic system and its variants	
	•	•	•	Warranty extension to 36 months on basic system and its variants	
NOTES					
For power consumption calculation we recommend to read the tips on pg. 4. The power values does not include the absorbed power of USB devices connected to the ports. 1: UPS module is supported by Microsoft Win32/64 operating systems. 2: Communication boards cannot be installed together. 3: RVL option is in addition to the DVI-D video output on the motherboard, let the installation of max 1 extractable drawer and have to be connected to a MHR100 or MKR100 monitor.					



TECHNICAL SPECIFICATIONS	
Case	Wall book mounting
Overall dimensions & weight	See details on the related section
Power supply	24VDC isolated • Input voltage: 18÷32V DC
UPS (optional)	12V DC UPS (Uninterruptible Power Supply) battery backup system Batteries module (optional): Pb, 12V/13A max, 2500mAh • Charge time 3h@25°C • Discharge time 15'@5A and 25°C • Lifetime 10years@25°C
Motherboard	"All-In-One" type • ASEM 1371
Watch dog	Time programmable
Intel platform	Processor Intel® Celeron® J1900 dual core 35W • Intel® Core® 6 th generation 35/45W Chipset Intel® HM170 or CM236 PCH (Platform Controller Hub)
Operating System	O.S. certified by ASEM: Microsoft Windows 10 IoT Enterprise 2016 32/64bit • Microsoft Windows 8.1 Industry Pro 32/64bit • Microsoft Windows 7 Pro/Ultimate 32/64bit • Microsoft Windows Embedded Standard 7E/7P 32/64 bit • Linux Other operating systems, such as VxWorks, QNX, etc., have not been certified by ASEM but they are reasonably supported by the Intel platform after verification of compatibility O.S. not supported by Intel platform: Microsoft Windows XP / 2000 / 98 / Microsoft Windows CE 5 / 6
Software	Remote assistance: ASEM UBIQUITY BASIC Win32/64 runtime license with ASEM sticker
Video controller	Intel® HD Graphics 510 integrated into Intel® Celeron™ microprocessor • 950MHz Intel® HD Graphics 530 integrated into Intel® Core™ microprocessor • 950MHz / 1GHz
Video RAM (shared)	Dynamic Video Memory Technology • Memory quantity is automatically selected by operating system
System memory	DDR4-2133 type • 2 SODIMM modules • min 4GB • max 32GB
Mass storage interfaces	2 x SATA III, 6Gb/s • 1 x mSATA SATA III, 6Gb/s
RAID controller	Integrated into chip Intel® HM170/CM236 PCH • Raid 0, 1
TPM	2x10 (2,54) Pin-strip connector for optional TPM module
Front signalling (LED)	Power ON • UPS • HDD activity • Over temperature / Battery fault • Watchdog / Reset factory default
Front buttons (with open door)	Power ON • System Reset • Watchdog Reset • Factory Default Reset
Expansion slots	1 x PCIe x4 (Gen 3) + 1 x PCI, with Intel HM170 PCH chipset or 2 x PCIe x4 (Gen 3), with Intel CM236 PCH chipset • for half size cards with power consumption max 5W each
On Top I/F	4 x Ethernet 10/100/1000 Mbps (RJ45), 3 x Intel® I210, 1 x Intel I219LM • 2 x USB 3.0 (Type A) • 2 x USB 2.0 (Type A) • 1 x RS232 (DB9M) • 1 x DVI-D Single Link (max resolution: 1920x1080 FullHD) optional: 1 or 2 x RVL OUT (RJ45), remotation (TX) up to 100 m of video DVI-D and USB 2.0 signals
On Front I/F (with open front door)	1 x slot CFast (bootable) • 1 x system battery slot (CR2032) • 1 x USB 3.0
Environmental specifications	Operating temperature: 0°C÷+50°C, 0°C÷+45°C with 24x7 HDD or with Core i7 processor, +5°C÷+45°C with standard HDD • Storage temperature: -10° ÷ +60°C • Humidity: 80% (non-condensing)
Approvals	CE (EN 55022, EN 61000-3-2/3, EN 55024, EN 60950-1) • cULus LISTED (UL61010) pending
Standard warranty	12 months • Warranty management by ASEM headquarters

OVERALL DIMENSIONS (mm)
