



## XM7 Industrial Monitors

### XM7 Industrial Monitors

	XM7W7	XM708	XM712	XM715	XM717	XM719
Dimensions	7” wide	8,4”	12,1”	15”	17”	19”
Technology	TFT 262 K colors			TFT 16,2 M colors	TFT 16,7 M colors	
Backlight	LED		CCFL (2 lamps)	LED		
Brightness cd/m2	500	450	370	350	380	400
Contrast	600:1			700:1	1000:1	
Viewing angle H-V	70-60	75-75	140-120		170-170	
Lamp life (min a 25°C)	50.000 hours					
Resolution (pixel)	800 x 480	800 x 600		1024 x 768	1280 x 1024	
Touch technology	Analog resistive (4 wires)		Analog resistive (5 wires)			
RS232 / USB interface	Yes					
USB frontal IP66 / USB rear (2.0)	1 x					
Green Led Power ON	1 x					
VGA/DVI-I */S- Video/Video composite	1 x (* digital signal only single-link)					
External (WxHxD)	228 x 155 x 66,7	250 x 190 x 66,7	336 x 256 x 56,7	425 x 300 x 57,2	446 x 346 x 59,7	508 x 384 x 64,2
Cut-out (WxH)	219 x 145	241 x 180	321 x 240	393 x 275	426 x 326	477 x 353
Power supply	18...30 Vdc max 50 W					
Power consumption (W)	30		35		45	
Protection degree	IP66 front					
Operating temperature (°C)	0...50					



## XM7 Industrial Monitors

Storage temperature (°C)	-20...+65					
Humidity	90%					
Weight (Kg)	2,2	2,6	4,0	6,0	7,5	9,0
Certifications	CE, Atex (Group II - cat.3 G D), Environmental EN60068-2-6/27/30, Immunity EN61000-6-2 / Emission EN 61000-6-4					
Optional Kit						
INOX version - True-flat Touch	Yes					
External power supply 220/24VDC	Yes					