


**Industrial Automation - Products & Configurations**
**MONITOR MT8**

Basic configuration	LCD TFT 8,4" • backlight LED • Touch-Screen • VGA and DVI-D input • 24V DC power supply • without cables • 12 months warranty
---------------------	---

**MONITOR MT8-R**

&gt; note 1

Basic configuration	LCD TFT 8,4" • backlight LED • Touch-Screen • <b>integrated remotation</b> • transmission module • VGA and DVI-D input • 24V DC power supply • without cables • 12 months warranty
---------------------	--

<b>DISPLAY</b>	8,4" LCD TFT 4:3 • SVGA, 800x600, 256K colors • backlight LED, 400 cd/m2 • Viewing angle L:R/U:L (typ): 60°:60°/45°:55°		
	12,1" LCD TFT 4:3 • SVGA, 800x600, 16M colors • backlight LED, 500 cd/m2 • Viewing angle L:R/U:L (typ.): 80°:80°/80°:60°		
	12,1" LCD TFT 4:3 • XGA, 1024x768, 16M colors • backlight LED, 600 cd/m2 • Viewing angle L:R/U:L (typ): 80°:80°/70°:70°		
	15" LCD TFT 4:3 • XGA, 1024x768, 16M colors • backlight LED, 450 cd/m2 • Viewing angle: L:R/U:L (typ): 80°:80°/70°:70°		
	17" LCD TFT 5:4 • SXGA, 1280x1024, 16M colors • 2 CCFL, 250 cd/m2 • Viewing angle L:R/U:L (typ): 80°:80°/80°:80°		
	19" LCD TFT 5:4 • SXGA, 1280x1024, 16M colors • 2 CCFL, 300 cd/m2 • Viewing angle L:R/U:L (typ): 80°:80°/80°:80°		

GFG &gt; note 2

<b>TOUCH-SCREEN</b>	No Touch-Screen	-	
	8,4" Touch-Screen • 5 wires resistive technology • USB I/F	no	
	12,1" Touch-Screen • 5 wires resistive technology • USB I/F	yes	
	15" Touch-Screen • 5 wires resistive technology • USB I/F	yes	
	17" Touch-Screen • 5 wires resistive technology • USB I/F	yes	
	19" Touch-Screen • 5 wires resistive technology • USB I/F	no	

<b>POWER SUPPLY</b>	24V DC • 8÷32V DC	
	110V/220V AC • 90÷264V AC • autoranging	

**CABLES for DIRECT CONNECTION > note 3**

<b>CABLES for DIRECT CONNECTION</b>	Kit cables 1,8mt VGA (VGA 1,8mt / USB 1,8mt)	
	Kit cables 1,8mt DVI (DVI 1,8mt / USB 1,8mt)	
	Kit cables 7,5mt VGA (VGA 10mt / USB 7,5mt) > note 4	
	Kit cables 7,5mt DVI (DVI 10mt / USB 7,5mt) > note 4	
	Kit cables 10mt VGA (VGA 10mt / USB 11mt amplified) > note 4	
	Kit cables 10mt DVI (DVI 10mt/ USB 11mt amplified) > note 4	

**CABLES for REMOTATION > note 3**

<b>PATCH CABLES for REMOTATION</b>	Kit cables 0,3mt (VGA 0,3mt / USB 0,5mt)	
	Kit cables 0,9mt (VGA 0,9mt / USB 0,9mt)	
	Kit cables 1,8mt (VGA 1,8mt / USB 1,8mt)	
<b>CABLES for REMOTATION</b>	Cable 15m • CAT6 SFTP type • black > note 5	
	Cable 20m • CAT6 SFTP type • black > note 5	
	Cable 30m • CAT6 SFTP type • black > note 5	
	Cable 40m • CAT5E SFTP type • white > note 5	

**OPTIONS**


<b>WARRANTY EXTENSION</b>	Warranty extension to 18 months on basic system and its variants	
	Warranty extension to 24 months on basic system and its variants	
	Warranty extension to 36 months on basic system and its variants	

**NOTES**

- 1: USB connection is granted for UBS 1.1 standard. No USB HUB device can be connected to the ports.**
- 2: Glass Film Glass (GFG) touch-screen option:** see pg.167 for the differences with standard touch-screen configuration
- 3: Patch cables for remotation are needed. Customer can buy from ASEM or supply it by other channels.**  
Remotation cable must be supplied by ASEM.
- 4: With kit cables 7,5mt, USB 1.1 standard is ensured**  
With kit cables 11mt, USB 2.0 standard is ensured; USB cable has an amplified signal repeater in the middle;  
Repeater has dimensions of (mm) 32x17x90; distance of the repeater from the edges is 5mt and 6mt
- 5: SFTP (Shielded Foil Twisted Pair) is for Ethernet cable and means that the cable is shielded and made by twisted pair copper wires.**



TECHNICAL SPECIFICATIONS	
Case	Panel mount
Overall dimensions & weight	See details on the related section
Front Panel	Aluminum / Polycarbonate Pantone 429C color
Touchscreen	5 wires resistive technology • on board controller • USB I/F
Frontal protection	IP65
Front interfaces	MT 1 x USB 2.0 (type-A); MT-R <b>1 x USB 1.1 (Type A);</b>
Rear interfaces	MT 1 x VGA analog (DB15F) • 1 x DVI-D Single Link • 3 x USB 2.0 (Type A) • 1 x USB 2.0 (HUB input, Typo B) MT-R 1 x RJ45 (remotation input) • <b>3 x USB 1.1 (Type A)</b>
Environmental specifications	Operating temperature: 0° ÷ +45°C • Storage temperature: -5 ÷ +60°C • Humidity: 80% (non-condensing)
Approvals	CE (EN 55022, EN 61000-3-2/3, EN 55024, EN 60950-1)
Standard warranty	12 months • Warranty management by ASEM headquarters

**DIMENSIONS (mm)**


LCD TFT	A	B	C	D	E	F	G	H	Weight (kg)
8,4"	250	210	230	190	10	60,5	19,3	6	3,1
12,1"	335	270	315	250	10	60,5	19,3	6	4,6
15"	390	315	370	295	10	60,5	19,3	6	5,3
17"	455	355	435	335	10	63,9	22,8	6	6,7
19"	490	388	470	368	10	69,9	28,8	6	7,3

**MT-R CONNECTIONS**

 MT-R  
with integrated  
receiver module

CAT5E / CAT6

 REMOTATION  
CABLE

 TRANSMISSION  
MODULE

VGA

USB

 PATCH  
CABLES


PC