



## XV7 VESA IPC Fanless

### XV7 VESA IPC Fanless

|  |                                       |
|--|---------------------------------------|
|  | <b>XV715</b>                          |
| <b>DisplaySize</b>                               | 15"                                   |
| <b>Technology</b>                                | TFT                                   |
| <b>Colors</b>                                    | 262 K                                 |
| <b>Backlight</b>                                 | LED                                   |
| <b>Life (min. at 25 °C)</b>                      | 50.000 h                              |
| <b>Resolution</b>                                | 1024 x 768 pixels                     |
| <b>Touch Screen Type</b>                         | Analog resistive (5 wires)            |
| <b>CPU Fanless</b>                               | Intel® ATOM Dual Core N-2800 1.86 GHz |
| <b>Chipset</b>                                   | Intel® NM10                           |
| <b>DMI</b>                                       | 2,5 GT/s                              |
| <b>RAM</b>                                       | up to 4 GB DDR3 DIMM 204 pin          |
| <b>Removable Hard disk / SSD (opt.)</b>          | min. 250 GB SATA 2,5" / SSD 16 GB     |
| <b>Compact Flash Slot Internal (opt.)</b>        | 1 x                                   |
| <b>Compact Flash Slot External (opt.)</b>        | 1 x                                   |
| <b>RS232 serial port</b>                         | 1 x                                   |
| <b>RS485 serial port</b>                         | 1 x                                   |
| <b>USB on front (2.0) IP66</b>                   | 1 x                                   |
| <b>USB on rear (2.0)</b>                         | 2 x                                   |
| <b>Green led on front</b>                        | 1 x                                   |
| <b>PS/2 keyboard / mouse port</b>                | -                                     |
| <b>Mini PCIe</b>                                 | 1 x                                   |
| <b>Wi-fi card (optional)</b>                     | miniPCIe 1 x                          |
| <b>Video port</b>                                | 1 x VGA                               |
| <b>Audio port</b>                                | -                                     |
| <b>Ethernet port RJ45</b>                        | 2 x Ethernet 10/100/1000 Mbit         |
| <b>External (W x H x D) (mm)</b>                 | 425 x 300 x 77 (mm)                   |
| <b>Cut-out (W x H) (mm)</b>                      | -                                     |
| <b>Back-up with battery</b>                      | 1 x                                   |
| <b>Power supply</b>                              | 18...30 Vdc max 85 W                  |
| <b>Power consumption (24 Vdc - basic config)</b> | 43 W                                  |
| <b>Protection level</b>                          | IP 66 on front / IP54 on rear         |
| <b>Storage temperature (°C)</b>                  | -20...+65                             |
| <b>Operating temperature (°C)</b>                | 0...+50                               |



## XV7 VESA IPC Fanless

|                         |  |
|-------------------------|--|
| <b>Weight (kg)</b>      | 7,5  |
| <b>Humidity</b>         | 90%  |
| <b>Certifications</b>   | CE, Environment EN 60068-2-6/27/30 / Immunity EN 61000-6-2 / Emissions 61000-6-4 |
| <b>Operating system</b> | Win7 - Wes7 - Wes 2009 - WinXP Professional for Embedded                         |